

TECHNICAL DATA SHEET

LU4EX IP65 / Xenon


VERSION - 06.06.2016

STANDARD LUMINAIRE

Reference	LU4EX
Protection Class	IP65
Lighting Source	Xenon (MAX. 5W)
Connector	Rigid Loop on B'Light conductor 16mm ²
Dimensions	37 x 37 mm
Standard Length	515 - 1010 - 1505 - 2000mm
Length on measure	on request up to 2990mm
Nb Lighting Unit	17 bulbs/m
Voltage	24V
Power	3W 5W 51W/m 85W/m
Connecting Cable	Both side: 20cm standard cable 2x2.5mm ²
Corner Profil	PE4
End Caps	REC4



LU4EX/ Xenon (M ax 5W)



FINISH


Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-enameling Powder Coating RAL Color Anodising

Glass Finishing

Standard	VRCE: Clear Glass
On request	VRME: Opaline

ON REQUEST : Without PE4 Corner / FCU Fixture Only



ON REQUEST

Fixation	Without PE4 Corner Profil / Only FCU Fixture
Connecting Plug	AMS / AF or AMS-E / AF-E
Dimming Option	Phase 220V, Dali, KNX <i>Ask technical departement for more information</i>

ON REQUEST: Connecting Plug

AF/AMS



AF-E/AMS-E (IP68)



LIGHTING SOURCE

Lighting Source	Xenon Long Life
Glass	Clear or Frosted
Power	3W 5W
Voltage	24V 24V
Beam Angle	360° 360°
Color Temperature	2300K 2400K
Light Output lm/unit	12.6lm 40lm
Lifetime	20'000h 20'000h

CERTIFICAT



AGABEKOV



AGABEKOV SA Manufacture 6, ROUTE DE COMPOIS
CH-1222 VÉSENAZ - GENEVA - SWITZERLAND
Tel. +41 22 752 47 45 Fax. +41 22 752 37 08
E - mail: info@agabekov.com



AGABEKOV SA Bureau d'etudes 6, ROUTE DE COMPOIS
CH-1222 VÉSENAZ - GENEVA - SWITZERLAND
Tel. +41 22 752 47 45 Fax. +41 22 752 37 08
Internet: www.agabekov.com

