

TECHNICAL DATA SHEET

LU4S IP20 / Soffite

VERSION - 27.04.2016

STANDARD LUMINAIRE

Reference	LU4S		
Protection Class	IP20		
Lighting Source	Soffite		
Connector	Festoon on B'Light conductor 16mm ²		
Dimensions	24 x 17mm		
Standard Length	330 - 670 - 1000 - 1330 - 1670 - 2000mm		
Length on measure	on request up to 3000mm		
Nb Lighting Unit	17 bulbs/m		
Voltage	24V		
Power	3W	5W	10W
	51 W/m	85 W/m	170 W/m
Connecting Cable	1m standard cable 2x2.5mm ²		

FINISH

Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-Enameling Powder Coating RAL Color Anodising Polished Aluminium Chrome Aspect Polished Aluminium Old Gold Aspect

ON REQUEST

Fixation	FCU (Width: +4mm)
Reflector	RIP
Cover	VRC (Clear Glass) / VRM (Opaline Glass) VSC (Clear Glass) / VSM (Opaline Glass)
End Caps	EU4 EU4C (For VSC/VSM Cover)
Connecting Plug	AMS / AF
Dimming Option	Phase 220V, Dali, KNX <i>Ask technical departement for more information</i>


LIGHTING SOURCE

Lighting Source	Soffite Standard			Soffite Long Life	
Glass	Clear or Frosted			Clear or Frosted	
Power	3W	5W	10W	5W	10W
Voltage	24V	24V	24V	24V	24V
Beam Angle	360°	360°	360°	360°	360°
Color Temperature	2400K	2500K	2600K	2600K	2700K
Light Output lm/unit	20lm	38lm	80lm	50lm	120lm
Lifetime	1'000h	1'000h	1'000h	3'000h	3'000h


CERTIFICAT




APPLICATION: Cornices, Windows, Balustrades



LU4S / Soffite




ON REQUEST: LU4S Fixation FCU




ON REQUEST: LU4S Cover

VRC (or VRM) Soffite 5W max.



VSC (or VSM) Soffite 5W max.



ON REQUEST: LU4S End Caps

EU4



EU4C



ON REQUEST : Connecting plug AF/AMS

